

EHB 11 BLM magic Electric Drilling/Chiseling Hammer, 230V, SDS-max

Item Number: 0008731

EHB 11 BLM magic

Maintenance-free time is money!

>> The innovative magic drilling and chiseling hammers save money because they lose no time due to maintenance and failures: The three-phase AC motor means that there is no changing of worn-out carbon brushes. Failures due to burnt-out windings in the rotor of the motor are likewise a thing of the past. On the other hand, the built-in frequency inverter is a very useful feature, since it means that magic electric hammers can be plugged in to a standard mains socket. <<



Additional Advantages

- No wear at all: non-contact rpm setting.
- Consistent and concentrated performance in hard and soft materials due to the new high-tech percussion system.
- Undoubtedly safer operation for the user due to the unique built-in converter: automatic voltage-matching protects against under- and over-voltages.
- The work becomes less tiring thanks to the individually adjustable Pro-Ergo® handle system: Quick and easy shifting of the holding position during the work means more can be done in the same time.
- Optionally can be equipped with SDS-max (BLM) or hexagonal tool shank (BL).

Description	Metric	Imperial
L x w x h (without tool)	620 x 105 x 245 mm	24.4 x 4.1 x 9.6 in
Shipping size (length)	765 mm	30.1 in
Shipping size (width)	165 mm	6.5 in
Shipping size (height)	450 mm	17.7 in
Weight without tool	11,7 kg	25.8 lb
Shipping weight (including packaging)	18,1 kg	39.9 lb
Shank	SDS-max mm	SDS-max in
Percussion rate (adjustable)	1.300 - 2.150 1/min	1,300 - 2,150 blows/min
Drill speed	140-225 1/min	140-225 rpm
Single stroke impact	19 (1,9) J (mkp)	14 ft lb/blow
Demolition performance	600 kg/h	1,320 lb/h
Drive engine	three-phase induction motor with inverter in series for alternating current 50/60 Hz with protective insulation	
Voltage	220 - 240 1~ V	220 - 240 1~ V
Rated current	7,5 A	7.5 A
Power draw (required generator output: 3,3 kW)	1,38 kW	1.85 hp
Percussion system	air-cushioned percussion system	
Drilling drive	with safety clutch and disconnectable drive shaft	
Sound power level conforming to EC guideline 84/537/EEC	93 dB(A)	93 dB(A)

Standard Package - EHB 11 BLM magic

incl. 5 m supply cable, injection-moulded carrycase with tool compartments, grease gun with 180 cm³ grease, instruction book and EC-Conformity Certificate

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Thursday, January 6, 2011

